



TECHNICAL DATA SHEET

EXOL MARINE TWO STROKE TC-W3

An API TC-W3 quality two stroke oil

Product code: M154

Product Description:

Exol Marine Two Stroke TC-W3 is a premium quality, specially formulated, outboard two stroke oil.

Exol Marine Two Stroke TC-W3 is manufactured from a special blend of highly refined mineral oils balanced proportionately with synthetic based ashless additives to provide superior protection and extend engine life. It exceeds the requirements of the widely quoted national Marine Manufacturers Association NMMA.

Benefits:

- Provides extended engine life through superior protection
- Non toxic to marine life
- Reduces spark plug fouling
- Extends valve life by reducing exhaust port deposits

Applications:

Exol Marine Two Stroke TC-W3 is suitable for the majority of water-cooled out board two strokes. It is suitable for high output engines ranging from 15 H.P up to and exceeding 70 H.P.

Always refer to the manufacturer's handbook for mixing ratios.

Product Specification

NMMA	TC-W3
API	TD

Typical Characteristics

Appearance	Amber
Specific Gravity @ 15.6°C	0.880
Kinematic Viscosity	
@ 100°C mm ² /s	8.51
Flash Point °C	120

Health & Safety: (Group 4M)

Please refer to the relevant health and safety data sheet, a copy of which is freely available to all of our customers

Availability:

Exol Marine Two Stroke TC-W3 is available in bulk road tanker deliveries, 205 litre barrels, and in 25 litre drums.

Issue No: e2
April 2006

Issued by: D Hall
Approved by: